

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Issued by DBI Certification, notified body No. 2531.

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

Vertical hollow straight signposts

Scope: **Supports supplied for fixed vertical signs (ZA.2)**

The product fulfils the essential characteristic:

See Annex 1

Intended use: **Stock Items (described by performance)**

Placed on the market under the name or trade mark of:

**Infra Group Danmark ApS
Højgårdsvej 11
5750 Ringe
Denmark**

and produced in the manufacturing plant:

CPA30005

This attests that all provisions concerning the performance described in Annex ZA of the standard(s)

EN 12899-1:2007 : **Fixed, vertical road traffic signs - Part 1: Fixed signs**

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

CONSTANCY OF PERFORMANCE OF THE CONSTRUCTION PRODUCT.

This certificate was first issued on 2017-09-14 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The attached annexes form part of this certificate.

Date of issue: **2024-04-26**

(This certificate supersedes the previous version of this certificate issued 2020-08-27)



Merete Poulsen
Responsible for evaluation



Lene Skovbjerg
Responsible for certification decision

The certificate shall be reproduced in extenso
– extracts only with written permission from DBI Certification A/S.

Annex 1

EXTENT

Type	Description																																																																																																																																																																								
<p>Dimensions: OD 33,7 x 3,2 mm OD 48,3 x 2,9 mm OD 48,3 x 3,0 mm OD 48,3 x 3,2 mm OD 48,3 x 4,0 mm OD 60,3 x 3,6 mm OD 60,3 x 4,5 mm OD 76,1 x 3,6 mm OD 76,1 x 4,5 mm OD 88,9 x 3,2 mm OD 88,9 x 4,0 mm OD 88,9 x 4,8 mm OD 114,3 x 4,5 mm OD 114,3 x 5,0 mm OD 114,3 x 5,4 mm</p> <p>Material: Steel S235JRH, S235JOH or S235J2H Hot dip galvanized coating, according to EN 1461.</p>	<p>Resistance to horizontal loads, bending, torsion:</p> <table border="1"> <thead> <tr> <th rowspan="2">Steel pipe mm</th> <th colspan="2">Bending</th> <th colspan="2">Torsion</th> </tr> <tr> <th>Max moment kNm</th> <th>Stiffness kNm²</th> <th>Max torque kNm</th> <th>Stiffness kNm²</th> </tr> </thead> <tbody> <tr><td>33,7 x 3,2</td><td>0,50</td><td>7,57</td><td>0,58</td><td>5,84</td></tr> <tr><td>48,3 x 2,9</td><td>1,04</td><td>22,5</td><td>1,20</td><td>17,3</td></tr> <tr><td>48,3 x 3,0</td><td>1,07</td><td>23,1</td><td>1,24</td><td>17,8</td></tr> <tr><td>48,3 x 3,2</td><td>1,13</td><td>24,3</td><td>1,30</td><td>18,8</td></tr> <tr><td>48,3 x 4,0</td><td>1,34</td><td>28,9</td><td>1,55</td><td>22,3</td></tr> <tr><td>60,3 x 3,6</td><td>2,02</td><td>54,3</td><td>2,33</td><td>41,9</td></tr> <tr><td>60,3 x 4,5</td><td>2,41</td><td>64,9</td><td>2,78</td><td>50,1</td></tr> <tr><td>76,1 x 3,6</td><td>3,34</td><td>113</td><td>3,85</td><td>87,5</td></tr> <tr><td>76,1 x 4,5</td><td>4,02</td><td>137</td><td>4,64</td><td>105</td></tr> <tr><td>88,9 x 3,2¹</td><td>4,19</td><td>166</td><td>4,84</td><td>128</td></tr> <tr><td>88,9 x 4,0</td><td>5,09</td><td>202</td><td>5,88</td><td>156</td></tr> <tr><td>88,9 x 4,8</td><td>5,95</td><td>236</td><td>6,87</td><td>182</td></tr> <tr><td>114,3 x 4,5</td><td>9,64</td><td>492</td><td>11,1</td><td>380</td></tr> <tr><td>114,3 x 5,0</td><td>10,6</td><td>540</td><td>12,2</td><td>416</td></tr> <tr><td>114,3 x 5,4</td><td>11,3</td><td>577</td><td>13,0</td><td>445</td></tr> </tbody> </table> <p>Performance under vehicle impact:</p> <table border="1"> <thead> <tr> <th>Steel pipe mm</th> <th>Speed class</th> <th>Energy absorption category</th> <th>Occupant safety level</th> <th>Collapse mode</th> </tr> </thead> <tbody> <tr><td>33,7 x 3,2</td><td>100</td><td>NE</td><td>C</td><td>SE</td></tr> <tr><td>48,3 x 2,9</td><td>100</td><td>NE</td><td>C</td><td>SE</td></tr> <tr><td>48,3 x 3,0</td><td>100</td><td>NE</td><td>C</td><td>SE</td></tr> <tr><td>48,3 x 3,2</td><td>100</td><td>NE</td><td>C</td><td>SE</td></tr> <tr><td>48,3 x 4,0</td><td>100</td><td>NE</td><td>C</td><td>SE</td></tr> <tr><td>60,3 x 3,6</td><td>100</td><td>NE</td><td>C</td><td>SE</td></tr> <tr><td>60,3 x 4,5</td><td>100</td><td>NE</td><td>C</td><td>SE</td></tr> <tr><td>76,1 x 3,6</td><td>100</td><td>NE</td><td>C</td><td>SE</td></tr> <tr><td>76,1 x 4,5</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>88,9 x 3,2²</td><td>100</td><td>NE</td><td>C</td><td>SE</td></tr> <tr><td>88,9 x 4,0</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>88,9 x 4,8</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>114,3 x 4,5</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>114,3 x 5,0</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>114,3 x 5,4</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>Durability:</p> <table border="1"> <tr> <td>Corrosion resistance (supports) Metal</td> <td>SP1</td> </tr> <tr> <td>Resistance to penetration of dust and water</td> <td>Supports can not be provided with compartments for electrical equipment</td> </tr> </table> <p>¹ Deemed to comply as class 100,NE,C according to EN 12767:2019, Annex K ² Deemed to comply as class 100,NE,C according to EN 12767:2019, Annex K</p>	Steel pipe mm	Bending		Torsion		Max moment kNm	Stiffness kNm ²	Max torque kNm	Stiffness kNm ²	33,7 x 3,2	0,50	7,57	0,58	5,84	48,3 x 2,9	1,04	22,5	1,20	17,3	48,3 x 3,0	1,07	23,1	1,24	17,8	48,3 x 3,2	1,13	24,3	1,30	18,8	48,3 x 4,0	1,34	28,9	1,55	22,3	60,3 x 3,6	2,02	54,3	2,33	41,9	60,3 x 4,5	2,41	64,9	2,78	50,1	76,1 x 3,6	3,34	113	3,85	87,5	76,1 x 4,5	4,02	137	4,64	105	88,9 x 3,2 ¹	4,19	166	4,84	128	88,9 x 4,0	5,09	202	5,88	156	88,9 x 4,8	5,95	236	6,87	182	114,3 x 4,5	9,64	492	11,1	380	114,3 x 5,0	10,6	540	12,2	416	114,3 x 5,4	11,3	577	13,0	445	Steel pipe mm	Speed class	Energy absorption category	Occupant safety level	Collapse mode	33,7 x 3,2	100	NE	C	SE	48,3 x 2,9	100	NE	C	SE	48,3 x 3,0	100	NE	C	SE	48,3 x 3,2	100	NE	C	SE	48,3 x 4,0	100	NE	C	SE	60,3 x 3,6	100	NE	C	SE	60,3 x 4,5	100	NE	C	SE	76,1 x 3,6	100	NE	C	SE	76,1 x 4,5	-	-	-	-	88,9 x 3,2 ²	100	NE	C	SE	88,9 x 4,0	-	-	-	-	88,9 x 4,8	-	-	-	-	114,3 x 4,5	-	-	-	-	114,3 x 5,0	-	-	-	-	114,3 x 5,4	-	-	-	-	Corrosion resistance (supports) Metal	SP1	Resistance to penetration of dust and water	Supports can not be provided with compartments for electrical equipment
Steel pipe mm	Bending		Torsion																																																																																																																																																																						
	Max moment kNm	Stiffness kNm ²	Max torque kNm	Stiffness kNm ²																																																																																																																																																																					
33,7 x 3,2	0,50	7,57	0,58	5,84																																																																																																																																																																					
48,3 x 2,9	1,04	22,5	1,20	17,3																																																																																																																																																																					
48,3 x 3,0	1,07	23,1	1,24	17,8																																																																																																																																																																					
48,3 x 3,2	1,13	24,3	1,30	18,8																																																																																																																																																																					
48,3 x 4,0	1,34	28,9	1,55	22,3																																																																																																																																																																					
60,3 x 3,6	2,02	54,3	2,33	41,9																																																																																																																																																																					
60,3 x 4,5	2,41	64,9	2,78	50,1																																																																																																																																																																					
76,1 x 3,6	3,34	113	3,85	87,5																																																																																																																																																																					
76,1 x 4,5	4,02	137	4,64	105																																																																																																																																																																					
88,9 x 3,2 ¹	4,19	166	4,84	128																																																																																																																																																																					
88,9 x 4,0	5,09	202	5,88	156																																																																																																																																																																					
88,9 x 4,8	5,95	236	6,87	182																																																																																																																																																																					
114,3 x 4,5	9,64	492	11,1	380																																																																																																																																																																					
114,3 x 5,0	10,6	540	12,2	416																																																																																																																																																																					
114,3 x 5,4	11,3	577	13,0	445																																																																																																																																																																					
Steel pipe mm	Speed class	Energy absorption category	Occupant safety level	Collapse mode																																																																																																																																																																					
33,7 x 3,2	100	NE	C	SE																																																																																																																																																																					
48,3 x 2,9	100	NE	C	SE																																																																																																																																																																					
48,3 x 3,0	100	NE	C	SE																																																																																																																																																																					
48,3 x 3,2	100	NE	C	SE																																																																																																																																																																					
48,3 x 4,0	100	NE	C	SE																																																																																																																																																																					
60,3 x 3,6	100	NE	C	SE																																																																																																																																																																					
60,3 x 4,5	100	NE	C	SE																																																																																																																																																																					
76,1 x 3,6	100	NE	C	SE																																																																																																																																																																					
76,1 x 4,5	-	-	-	-																																																																																																																																																																					
88,9 x 3,2 ²	100	NE	C	SE																																																																																																																																																																					
88,9 x 4,0	-	-	-	-																																																																																																																																																																					
88,9 x 4,8	-	-	-	-																																																																																																																																																																					
114,3 x 4,5	-	-	-	-																																																																																																																																																																					
114,3 x 5,0	-	-	-	-																																																																																																																																																																					
114,3 x 5,4	-	-	-	-																																																																																																																																																																					
Corrosion resistance (supports) Metal	SP1																																																																																																																																																																								
Resistance to penetration of dust and water	Supports can not be provided with compartments for electrical equipment																																																																																																																																																																								

The certificate shall be reproduced in extenso
 – extracts only with written permission from DBI Certification A/S.

Annex 1

EXTENT

Type	Description																																												
Dimensions IPE-profiles: IPE 120 IPE 140 IPE 160 IPE 180 IPE 200 IPE 220 IPE 240 Material: Steel S355J2 Hot dip galvanized coating, according to EN 1461	Resistance to horizontal loads, bending, torsion: <table border="1"> <thead> <tr> <th rowspan="2">IPE No.</th> <th colspan="2">Bending</th> <th colspan="2">Torsion</th> </tr> <tr> <th>Max moment kNm</th> <th>Stiffness kNm²</th> <th>Max torque kNm</th> <th>Stiffness kNm²</th> </tr> </thead> <tbody> <tr><td>120</td><td>18,8</td><td>668</td><td>0,57</td><td>1,41</td></tr> <tr><td>140</td><td>27,4</td><td>1136</td><td>0,73</td><td>1,98</td></tr> <tr><td>160</td><td>38,7</td><td>1825</td><td>1,00</td><td>2,93</td></tr> <tr><td>180</td><td>51,8</td><td>2772</td><td>1,23</td><td>3,89</td></tr> <tr><td>200</td><td>68,9</td><td>4074</td><td>1,69</td><td>5,69</td></tr> <tr><td>220</td><td>89,5</td><td>5817</td><td>2,03</td><td>7,37</td></tr> <tr><td>240</td><td>115,0</td><td>8169</td><td>2,70</td><td>10,45</td></tr> </tbody> </table>	IPE No.	Bending		Torsion		Max moment kNm	Stiffness kNm ²	Max torque kNm	Stiffness kNm ²	120	18,8	668	0,57	1,41	140	27,4	1136	0,73	1,98	160	38,7	1825	1,00	2,93	180	51,8	2772	1,23	3,89	200	68,9	4074	1,69	5,69	220	89,5	5817	2,03	7,37	240	115,0	8169	2,70	10,45
	IPE No.		Bending		Torsion																																								
		Max moment kNm	Stiffness kNm ²	Max torque kNm	Stiffness kNm ²																																								
	120	18,8	668	0,57	1,41																																								
	140	27,4	1136	0,73	1,98																																								
	160	38,7	1825	1,00	2,93																																								
	180	51,8	2772	1,23	3,89																																								
	200	68,9	4074	1,69	5,69																																								
	220	89,5	5817	2,03	7,37																																								
	240	115,0	8169	2,70	10,45																																								
Durability: <table border="1"> <tr> <td>Corrosion resistance (supports) Metal</td> <td>SP1</td> </tr> </table>		Corrosion resistance (supports) Metal	SP1																																										
Corrosion resistance (supports) Metal	SP1																																												
<table border="1"> <tr> <td>Resistance to penetration of dust and water</td> <td>Supports can not be provided with compartments for electrical equipment</td> </tr> </table>		Resistance to penetration of dust and water	Supports can not be provided with compartments for electrical equipment																																										
Resistance to penetration of dust and water	Supports can not be provided with compartments for electrical equipment																																												

Type	Description																																																																																				
Dimensions RHS-profiles: RHS 60 x 40 x 3,0 RHS 80 x 40 x 3,0 RHS 100 x 50 x 3,0 RHS 120 x 60 x 4,0 RHS 150 x 100 x 5,0 RHS 160 x 80 x 5,0 RHS 180 x 100 x 6,0 RHS 200 x 100 x 6,0 RHS 250 x 150 x 6,3 RHS 100 x 100 x 5,0 RHS 120 x 120 x 5,0 RHS 150 x 150 x 5,0 RHS 180 x 180 x 5,0 RHS 200 x 200 x 5,0 RHS 200 x 200 x 8,0 Material: Steel S355J2 Hot dip galvanized coating, according to EN 1461	Resistance to horizontal loads, bending, torsion: <table border="1"> <thead> <tr> <th rowspan="2">RHS No.</th> <th colspan="2">Bending</th> <th colspan="2">Torsion</th> </tr> <tr> <th>Max moment kNm</th> <th>Stiffness kNm²</th> <th>Max torque kNm</th> <th>Stiffness kNm²</th> </tr> </thead> <tbody> <tr><td>60x40x3,0</td><td>3,1</td><td>56</td><td>2,3</td><td>24</td></tr> <tr><td>80x40x3,0</td><td>4,8</td><td>114</td><td>3,1</td><td>35</td></tr> <tr><td>100x50x3,0</td><td>7,8</td><td>231</td><td>5,1</td><td>72</td></tr> <tr><td>120x60x4,0</td><td>14,7</td><td>523</td><td>9,7</td><td>163</td></tr> <tr><td>150x100x5</td><td>35,0</td><td>1552</td><td>26,0</td><td>654</td></tr> <tr><td>160x80x5,0</td><td>33,0</td><td>1562</td><td>21,7</td><td>486</td></tr> <tr><td>180x100x6,0</td><td>53,3</td><td>2835</td><td>36,7</td><td>988</td></tr> <tr><td>200x100x6,0</td><td>62,1</td><td>3675</td><td>41,0</td><td>1142</td></tr> <tr><td>250x150x6,3</td><td>117,5</td><td>8694</td><td>84,6</td><td>3281</td></tr> <tr><td>100x100x5,0</td><td>19,8</td><td>586</td><td>16,8</td><td>356</td></tr> <tr><td>120x120x5,0</td><td>29,5</td><td>1046</td><td>25,0</td><td>629</td></tr> <tr><td>150x150x5,0</td><td>47,6</td><td>2100</td><td>40,4</td><td>1256</td></tr> <tr><td>180x180x5,0</td><td>69,6</td><td>3717</td><td>59,5</td><td>1434</td></tr> <tr><td>200x200x5,0</td><td>87,0</td><td>5145</td><td>74,2</td><td>3046</td></tr> <tr><td>200x200x8,0</td><td>131,7</td><td>7791</td><td>111,7</td><td>4682</td></tr> </tbody> </table>	RHS No.	Bending		Torsion		Max moment kNm	Stiffness kNm ²	Max torque kNm	Stiffness kNm ²	60x40x3,0	3,1	56	2,3	24	80x40x3,0	4,8	114	3,1	35	100x50x3,0	7,8	231	5,1	72	120x60x4,0	14,7	523	9,7	163	150x100x5	35,0	1552	26,0	654	160x80x5,0	33,0	1562	21,7	486	180x100x6,0	53,3	2835	36,7	988	200x100x6,0	62,1	3675	41,0	1142	250x150x6,3	117,5	8694	84,6	3281	100x100x5,0	19,8	586	16,8	356	120x120x5,0	29,5	1046	25,0	629	150x150x5,0	47,6	2100	40,4	1256	180x180x5,0	69,6	3717	59,5	1434	200x200x5,0	87,0	5145	74,2	3046	200x200x8,0	131,7	7791	111,7	4682
	RHS No.		Bending		Torsion																																																																																
		Max moment kNm	Stiffness kNm ²	Max torque kNm	Stiffness kNm ²																																																																																
	60x40x3,0	3,1	56	2,3	24																																																																																
	80x40x3,0	4,8	114	3,1	35																																																																																
	100x50x3,0	7,8	231	5,1	72																																																																																
	120x60x4,0	14,7	523	9,7	163																																																																																
	150x100x5	35,0	1552	26,0	654																																																																																
	160x80x5,0	33,0	1562	21,7	486																																																																																
	180x100x6,0	53,3	2835	36,7	988																																																																																
	200x100x6,0	62,1	3675	41,0	1142																																																																																
	250x150x6,3	117,5	8694	84,6	3281																																																																																
	100x100x5,0	19,8	586	16,8	356																																																																																
	120x120x5,0	29,5	1046	25,0	629																																																																																
	150x150x5,0	47,6	2100	40,4	1256																																																																																
	180x180x5,0	69,6	3717	59,5	1434																																																																																
	200x200x5,0	87,0	5145	74,2	3046																																																																																
	200x200x8,0	131,7	7791	111,7	4682																																																																																
	Durability: <table border="1"> <tr> <td>Corrosion resistance (supports) Metal</td> <td>SP1</td> </tr> </table>		Corrosion resistance (supports) Metal	SP1																																																																																	
	Corrosion resistance (supports) Metal	SP1																																																																																			
<table border="1"> <tr> <td>Resistance to penetration of dust and water</td> <td>Supports can not be provided with compartments for electrical equipment</td> </tr> </table>		Resistance to penetration of dust and water	Supports can not be provided with compartments for electrical equipment																																																																																		
Resistance to penetration of dust and water	Supports can not be provided with compartments for electrical equipment																																																																																				

The certificate shall be reproduced in extenso
 – extracts only with written permission from DBI Certification A/S.

Annex 2

TEST DOCUMENTATION

EN 12767:2007, Annex F- Deemed to comply
--

Annex 3

TECHNICAL BASIS

File number	Title	Date
None	Infra Group Danmark ApS, CE marking and labeling Traffic signs - nomograms for calculation of hollow steel pipes for smaller sign sizes, Verification of the physical performance by calculation in accordance with EN 12899-1:2007.	November 2015
None	Infra Group Danmark A/S, CE marking and labeling Traffic signs - nomograms for calculation of hollow steel pipes for medium sign sizes, Verification of the physical performance by calculation in accordance with EN 12899-1:2007.	November 2015
None	Resistance to horizontal loads	2016-04-25
None	Annex 1	2016-04-25
None	Performance under vehicle impact	2016-04-25
None	Regarding change request for Certificate No. 2531-CPR-CSC10013, Addendum to Annex 1	2020-01-23

The certificate shall be reproduced in extenso
 – extracts only with written permission from DBI Certification A/S.